

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MaskingInk**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Professional use

1.3 Details of the supplier of the safety data sheet

POLYCHROMAL B.V.
PO Box: 8043
1802 KA
Alkmaar

Telephone: +31 72 5670799
Telefax: +31 72 5624095
e-mail: products@polychromal.nl
Website: www.polychromal.com

e-mail (competent person) products@polychromal.nl

1.4 Emergency telephone number

Emergency information service +31 72 5670799
This number is only available during the following office hours: Mon-Fri 08:00 - 17:00

Poison centre		
Country	Name	Telephone
United Kingdom	National Poisons Information Service (NPIS)	0344-8920111 (medical professionals only)
United Kingdom	NHS (general public)	non-emergency: 111 or a doctor; emergency: 999

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (acc. to GB CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.10	acute toxicity (oral)	4	Acute Tox. 4	H302
3.11	acute toxicity (inhal.)	3	Acute Tox. 3	H331
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of H-phrases: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

2.2 Label elements

Labelling (acc. to GB CLP)

- signal word Danger

- pictograms

GHS06



- hazard statements

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H412 Harmful to aquatic life with long lasting effects.

- precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P311 Call a POISON CENTER/doctor.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- hazardous ingredients for labelling

Contains: 2-butoxyethanol.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.





SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Hydrocarbons, C10 aromatics, <1% naphthalene	EC No 918-811-1	2.275 – 4.55	STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411 EUH066	  	
2-butoxyethanol	CAS No 111-76-2		Acute Tox. 4 / H302 Acute Tox. 3 / H331 Skin Irrit. 2 / H315		

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
	EC No 203-905-0 Index No 603-014-00-0		Eye Irrit. 2 / H319		

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
2-butoxyethanol	CAS No 111-76-2 EC No 203-905-0	-	-	1,200 mg/kg 3 mg/l/4h	oral inhalation: vapour

Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Immediately call a POISON CENTER/doctor.

Following skin contact

Wash with plenty of soap and water. Call a POISON CENTER/doctor.

Following eye contact

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray; Dry extinguishing powder; Carbon dioxide (CO₂);
Co-ordinate firefighting measures to the fire surroundings.

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

During fire hazardous fumes/smoke could be produced. Carbon monoxide (CO). Carbon dioxide (CO₂).

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- incompatible substances or mixtures

Keep away from alkalis, oxidising substances, acids.

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Control of effects

Protect against external exposure, such as
High temperatures. UV-radiation/sunlight.

Consideration of other advice

Store in a well-ventilated place. Keep container tightly closed.

- ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted.

- packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Notation	Source
GB	2-butoxyethanol	111-76-2	WEL	25	123	50	246	H	EH40/2005

Notation

H absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
GB	2-butoxyethanol	2-butoxyacetic acid	crea	BMGV	240 mmol/mol	EH40/2005

Notation

crea creatinine

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-butoxyethanol	111-76-2	DNEL	125 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	89 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
2-butoxyethanol	111-76-2	DNEL	75 mg/kg	human, dermal	consumer (private)	chronic - systemic

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
			bw/day		households)	effects
2-butoxyethanol	111-76-2	DNEL	89 mg/kg bw/day	human, dermal	consumer (private households)	acute - systemic effects
2-butoxyethanol	111-76-2	DNEL	98 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	1,091 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
2-butoxyethanol	111-76-2	DNEL	246 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-butoxyethanol	111-76-2	DNEL	59 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	426 mg/m ³	human, inhalatory	consumer (private households)	acute - systemic effects
2-butoxyethanol	111-76-2	DNEL	147 mg/m ³	human, inhalatory	consumer (private households)	acute - local effects
2-butoxyethanol	111-76-2	DNEL	6.3 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	26.7 mg/kg bw/day	human, oral	consumer (private households)	acute - systemic effects
Hydrocarbons, C10 aromatics, <1% naphthalene		DNEL	151 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C10 aromatics, <1% naphthalene		DNEL	12.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C10 aromatics, <1% naphthalene		DNEL	32 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
Hydrocarbons, C10 aromatics, <1% naphthalene		DNEL	7.5 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
Hydrocarbons, C10 aromatics, <1% naphthalene		DNEL	7.5 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects

Relevant PNECs of components						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxyethanol	111-76-2	PNEC	9.1 mg/l	aquatic organisms	water	intermittent release
2-butoxyethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	463 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	34.6 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxyethanol	111-76-2	PNEC	3.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	2.33 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation. Provide eyewash stations and safety showers at the workplace.

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection

Skin protection



Chemical protective clothing.

Hand protection



Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- type of material

Nitrile rubber

- material thickness

Use gloves with a minimum material thickness: ≥ 0.38 mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	various
Odour	characteristic
Melting point/freezing point	-74.8 °C at 1 atm calculated value, referring to a component of the mixture
Boiling point or initial boiling point and boiling range	>171 °C at 1 atm calculated value, referring to a component of the mixture
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	LEL: 0.6 vol% / UEL: 7 vol% calculated value, referring to a component of the mixture
Flash point	65 °C at 1 atm calculated value, referring to a component of the mixture
Auto-ignition temperature	230 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture
Decomposition temperature	no data available
pH (value)	not determined
Kinematic viscosity	not determined
Solubility	not determined

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	0.09 kPa at 20 °C calculated value, referring to a component of the mixture
-----------------	--

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Harmful if swallowed. Toxic if inhaled.

- acute toxicity estimate (ATE)

Exposure route	ATE
Oral	1,319 mg/kg
Inhalation: vapour	3.297 mg/l/4h

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
2-butoxyethanol	111-76-2	oral	1,200 mg/kg
2-butoxyethanol	111-76-2	inhalation: vapour	3 mg/l/4h

Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
2-butoxyethanol	111-76-2	dermal	LD50	>2,000 mg/kg	rat

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
2-butoxyethanol	111-76-2	oral	LD50	1,414 mg/kg	guinea pig
Hydrocarbons, C10 aromatics, <1% naphthalene		oral	LD50	7,093 mg/kg	rat
Hydrocarbons, C10 aromatics, <1% naphthalene		dermal	LD50	>3,160 mg/kg	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxyethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxyethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h
2-butoxyethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
2-butoxyethanol	111-76-2	NOEC	88 mg/l	algae	72 h
2-butoxyethanol	111-76-2	growth (EbCx) 10%	308 mg/l	algae	72 h
2-butoxyethanol	111-76-2	growth rate (Er-Cx) 10%	679 mg/l	algae	72 h

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C10 aromatics, <1% naphthalene		LL50	≤5 mg/l	fish	96 h
Hydrocarbons, C10 aromatics, <1% naphthalene		EL50	≤10 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C10 aromatics, <1% naphthalene		NOELR	1 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxyethanol	111-76-2	EC50	297 mg/l	aquatic invertebrates	21 d
2-butoxyethanol	111-76-2	NOEC	100 mg/l	aquatic invertebrates	21 d
2-butoxyethanol	111-76-2	growth (EbCx) 10%	134 mg/l	aquatic invertebrates	21 d
Hydrocarbons, C10 aromatics, <1% naphthalene		NOELR	0.441 mg/l	fish	28 d

12.2 Persistence and degradability

Degradability of components					
Name of substance	CAS No	Process	Degradation rate	Time	Method
2-butoxyethanol	111-76-2	carbon dioxide generation	18.3 %	3 d	
Hydrocarbons, C10 aromatics, <1% naphthalene		oxygen depletion	1.79 %	5 d	

12.3 Bioaccumulative potential

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
2-butoxyethanol	111-76-2		0.81 (pH value: 7, 25 °C)	
Hydrocarbons, C10 aromatics, <1% naphthalene		≥70 – ≤560	≥3.17 – ≤4.18 (pH value: ~7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0,1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

12.7 Other adverse effects

Data are not available.

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

ADR/RID	UN 2810
IMDG-Code	UN 2810
ICAO-TI	UN 2810

14.2 UN proper shipping name

ADR/RID	TOXIC LIQUID, ORGANIC, N.O.S.
IMDG-Code	TOXIC LIQUID, ORGANIC, N.O.S.
ICAO-TI	Toxic liquid, organic, n.o.s.

14.3 Transport hazard class(es)

ADR/RID	6.1
IMDG-Code	6.1
ICAO-TI	6.1

14.4 Packing group

ADR/RID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

No data available.

Additional information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - additional information

Classification code	T1
Danger label(s)	6.1

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16



Special provisions (SP)	274, 614, 802(ADN)
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	2
Tunnel restriction code (TRC)	E
Hazard identification No	60
Emergency Action Code	2X

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - additional information

Classification code	T1
Danger label(s)	6.1



Special provisions (SP)	274, 614, 802(ADN)
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	2
Hazard identification No	60

International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant	-
Danger label(s)	6.1



Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-A
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Danger label(s)	6.1
-----------------	-----



Special provisions (SP)	A3, A4, A137
Excepted quantities (EQ)	E1
Limited quantities (LQ)	2 L

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
H2	acute toxic (cat. 2 + cat. 3, inhal.)	50	200	41)

Notation

- 41) - category 2, all exposure routes
- category 3, inhalation exposure route

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
2-butoxyethanol	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

Legend

- a) Indicative list of the main pollutants

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

None of the ingredients are listed.

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name	Name acc. to inventory	Conditions of restriction	No
MaskingInk	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Legend

R3

1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and,
 - present an aspiration hazard and are labelled with R65 or H304,
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the British Standard Specification on Decorative oil lamps (BS EN 14059) adopted by the British Standards Institute.
5. Without prejudice to the implementation of other legislation relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010 'Just a sip of lamp oil
 - or even sucking the wick of lamps
 - may lead to life-threatening lung damage';
 - (b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life-threatening lung damage';
 - (c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the Agency.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Abbr.	Descriptions of used abbreviations
	test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NOELR	No Observed Effect Loading Rate
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

MaskingInk

Version number: 1.0

Date of compilation: 2024-10-16

Abbr.	Descriptions of used abbreviations
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended). The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended). GB mandatory classification and labelling.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.